

LINER 350 LINER 550

Tread sides sanding machine

TREAD SIDES SANDING MACHINE FOR PRECURED TREAD STRIPS

Larghezza max. battistrada *Max. tread width* 500 mm.



Tappeto per movimento fascia prestampata a velocità variabile.

Velocità media 11 m/min. Motore da 0.5 hp.

Precured tread is moved by a variable speed conveyor.

Average speed 11 m./min. 0.5 HP motor.

Utensili: 2 mole in carbide dia. 100 x 38 mm

Tools: 2 carbide tools dia. 100 x 38 mm

2 Motori per mole carbide: 0.5HP, 2 poli cad.

2 motors for carbide tool control: 0.5HP, 2 poles ea.

Alimentaz. aria compres. 6 - 8 bar 90 - 120 PSI.
Compressed air supply

Consumo aria compr. 130 NI/cycle
Compress. air absorption (4.60 cu ft/cycle)

Peso netto 650 kg. - 1080 lbs.
Net weight



MACCHINE PER PNEUMATICI E PER I PROCESSI DI RICOSTRUZIONE
EQUIPMENT FOR THE TYRE AND RETREADING INDUSTRIES

matteuzzi srl

Via Serra, 1/E - 3

40012 CALDERARA DI RENO, ITALY

Phone ++39 - 051726351

matteuzzi@matteuzzi-srl.com - www.matteuzzi-srl.com

Due to a policy of continuous improvement, the machine may differ from the images shown

LINER 350 LINER 550

*Tread sides sanding
machine*

TREAD SIDES SANDING MACHINE FOR PRECURED TREAD STRIPS

DIMENSIONI DELLA MACCHINA IN SERVIZIO (esempio)

DIMENSIONS OF THE MACHINE IN SERVICE (example)

